

## Technical Data Sheet

Part No.: 33979; 33980

Product Code: REV-5POL/05 ON/OFF;  
REV-5POL/07 ON/OFF

### Main switch / Emergency-off switch

4 pole + 1NC + 1NO


Switching angle 90°

Inscription 1 ON -- 0 OFF

Mounting ASA-PC blend plastic yellow UV-resistant  
lockout handle enclosure for 3 padlock red  
0-position 90° clock

Protection

IP65



### Electrical data

Rated uninterrupted current $I_{the}$ :	20 A
Rated operational current $I_e$ AC-21:	20 A
Rated operational voltage $U_e$ :	500 V
Making/breaking capacity of AC 3 / 400 V:	5,5 kW
Making/breaking capacity of AC23 B(A) / 400 V:	7,5 kW
Isolating characteristics achieved to	500 V

### Cross section

solid or stranded:	1,0 – 4mm <sup>2</sup>	tighten to 0,8Nm
stranded wire with sleeve:	1,0 – 2,5mm <sup>2</sup>	tighten to 0,8Nm

### Max. Cable cross-sections according to standard cable entries:

M12:	Ø3 – Ø 6,5 mm
M20:	Ø 6 – Ø 12 mm

Abmessung (mm)			Dimensions (mm)			
A	C	D	E	G	H1	H2
90,5	73	29	80	Ø5,5	M20	M12

